

C6.3 Drilled shafts

See the Office of Bridges and Structures web site for archived Methods Memos listed under articles in this section.

C6.3.1 General

C6.3.1.1 Policy overview

C6.3.1.2 Design information

C6.3.1.3 Definitions

C6.3.1.4 Abbreviations and notation

C6.3.1.5 References

C6.3.2 Loads

C6.3.3 Load application

C6.3.3.1 Load modifier

C6.3.3.2 Limit states

C6.3.4 Analysis and design

Methods Memo No. 54: Drilled Shaft Guidelines
5 November 2001

Memo 6.3.4, 11.8.1, and 11.8.2-2011 ~ Grooving of Drilled Shaft Rock Sockets

Whether grooving of the sidewalls of a rock socket is appropriate depends on the hardness of the rock. If the rock is soft, grooving is required; if the rock is hard, grooving is not feasible. Because grooving inadvertently was not specified for a few projects with soft rock sockets, the Office of Construction requested a specification change to make grooving (rather than not grooving) the standard. Thus, for hard rock sockets, the designer will need to include a note on the plans to omit grooving. The Soils Design Section will determine the need for grooving and provide the decision to the designer. All rock sockets, whether grooved or not, are intended to be brushed.

C6.3.5 Detailing